

EXTERNAL HARD DRIVE



120GB **200**GB

Perfect for video editing and high-end graphics Exclusive Maxtor OneTouch

Room to Create

The Maxtor external hard drive makes it easy to add blazing fast storage specially designed for your unique creative requirements. With storage capacities up to 200GB, you'll have plenty of workspace for all your large projects, including over 15 hours of digital video. The Maxtor 7200 RPM hard drive plus both FireWire® (IEEE 1394, i.LINK®) and USB 2.0 interface ports gives you one of the most versatile drives available for your Mac and PC.

The Best Ideas Need a Maxtor OneTouch Drive



Easy—Just push the button to make a backup copy of your files.

Fast—Back up files faster than floppy, CD or removable cartridge systems.

Convenient—Make backup copies of your files, while you work, with a simple push of a button.

Flexible—Use the Maxtor OneTouch button or run automated, unattended backups with Dantz® Retrospect® Express.


Features

- Versatile add-on storage for editing videos and high-end graphic files
- Maxtor OneTouch™: the easy way to make backup copies of your files
- Dantz® Retrospect® Express software included
- Quick and easy installation
- Flexible dual interfaces—FireWire® and USB 2.0/1.1 compatible
- Powerful performance—7200 RPM
- **■** Expandable storage
- Stands vertically or horizontally
- Hot-swappable
- Compact design
- PC and Mac compatible



Quick and Easy Installation







Push the button and follow the on-screen directions



Perfect for Video Editing and Graphics

These applications require a large amount of storage space and high sustained data transfer rates and the Maxtor external hard drive offers both.

Kit Includes

- Maxtor Personal Storage[™] 5000 drive
- USB Cable
- 6 pin to 6 pin FireWire/1394/i.LINK cable
- · External AC power adapter
- Vertical stand
- Installation software CD
 - Dantz Retrospect Express
 - Maxtor Personal Storage 5000 drivers
- · User's guide

Maydor Maydor Maydor O minimum of the state of the sta

- Stack drives for extra capacity
- Connect up to 62 FireWire drives

Windows System Requirements

- Pentium II-class equivalent processor or later
- Windows® 98SE, Me, 2000, or XP
- . CD-ROM drive
- 32 MB RAM or more as required by Windows
- Available FireWire/1394/i.LINK (OHCI-compliant) or USB 1.1 or 2.0 port
- · Internet connection (for system updates)

For faster operation, upgrade from USB 1.1 to high-speed USB 2.0 with a Maxtor USB 2.0 PCI Card for Windows or add a FireWire port to your PC with Maxtor's 1394/FireWire PCI Card. Both are available at www.maxtor.com in North America.

Macintosh System Requirements

- iMac®, Power Macintosh® G3 (Blue and White), or later model
- Mac OS 9.1 or higher or Mac OS X version 10.1.2 or higher, including Jaguar
- CD-ROM drive
- 32 MB RAM or more as required by Mac OS
- Available FireWire/1394/i.LINK (OHCI-compliant) or USB 1.1 or 2.0 port
- Internet connection (for system updates)

For support or information, call us at 1-800-2MAXTOR or visit us at www.maxtor.com

A megabyte means 1,000,000 bytes. A gigabyte means 1,000,000 bytes. Total accessible capacity varies depending on operating environment. A patent is pending on the Maxtor OneTouch™ drive.

SPECIFICATIONS

Drive Configuration

	120GB	200GB
Model Number	T01J120	T01P200
Hard drive	DiamondMax Plus with Ultra ATA/133	DiamondMax Plus with Ultra ATA/133
	interface	interface
RPM	7200	7200
Cache Buffer	2 MB	8 MB

Integrated Interface

- FireWire, IEEE 1394, i.LINK and SBP-2 compliant
 - External 6-pin 1394 connectors (2) with hot-plug capability
 - Supports serial bus data transfer rates of 100, 200 and 400 Mb/sec
- USB 2.0 and 1.1 compliant
 - External 4-pin connector with hot-plug capability
 - Supports data transfer rates up to 480 Mb/sec

Performance

- Average seek time: < 9 ms
- Sustained transfer rate (maximum):
 - USB2-34 MB/sec
 - FireWire-40 MB/sec
- Bus transfer rate (maximum):
 - USB2-480 Mb/sec
 - FireWire-400 Mb/sec

Environmental Specifications

• Operating temperature: 5° C to 40° C

Physical Specifications

- Dimensions: 1 5/8 x 6 x 8 5/8 inches (41 x 152 x 219 mm)
- Weight: 2 lbs, 11 oz (1.22 Kgrams)

Power Requirements

- AC Input Voltage: 100 240 VAC
- Input Frequency: 47 63 Hz AC















